



HIAB

PERFIL DE CARGA TOTAL AGI 13.5s

Departamento de Produtos


T Ponto Teórico

H Lança Hidráulica

C Pega na Capa de Lança


M Lança Manual

4H2M




[m]	[kg]
2,00	6.480 T
2,50	5.611
3,00	4.741
3,50	3.872
3,80	3.350 C
4,00	3.210
4,50	2.860
5,00	2.510
5,20	2.370 H
5,50	2.258
6,00	2.071
6,50	1.885
6,70	1.810 H
7,00	1.738
7,50	1.618
8,00	1.497
8,30	1.425 H
8,50	1.388
9,00	1.296
9,50	1.204
9,90	1.130 H
10,00	1.115
10,50	1.038
11,00	962
11,50	886
11,70	855 M
12,00	816
12,50	750
13,00	684
13,50	618
13,60	605 M

4H1M



[m]	[kg]
2,00	6.490 T
2,50	5.629
3,00	4.768
3,50	3.907
3,80	3.390 C
4,00	3.250
4,50	2.900
5,00	2.550
5,20	2.410 H
5,50	2.298
6,00	2.111
6,50	1.925
6,70	1.850 H
7,00	1.778
7,50	1.658
8,00	1.537
8,30	1.465 H
8,50	1.428
9,00	1.336
9,50	1.244
9,90	1.170 H
10,00	1.154
10,50	1.077
11,00	999
11,50	921
11,70	890 M

3H2M



[m]	[kg]
2,00	6.500 T
2,50	5.644
3,00	4.789
3,50	3.933
3,80	3.420 C
4,00	3.280
4,50	2.930
5,00	2.580
5,20	2.440 H
5,50	2.328
6,00	2.141
6,50	1.955
6,70	1.880 H
7,00	1.808
7,50	1.688
8,00	1.567
8,30	1.495 H
8,50	1.458
9,00	1.366
9,50	1.274
9,90	1.200 M
10,00	1.184
10,50	1.107
11,00	1.029
11,50	951
11,70	920 M